



		233.860		
+185			1.58	
3+200			0.76	
+211	SIDE ROAD LT & RT		0.34	
BM#14	3.252	235.528	1.584	232.276 232.276
+215			1.74	
TP	4.17	239.178	0.52	235.008
+222			3.81	
+230			2.38	

1.25	2.27	2.22	1.56	3.04	1.58	2.83	1.40	1.52	0.64	0.60
30	22	12	8	4	0	3.6	11	17	24	30
+2.04	+0.21	+0.57	0.0	1.09	0.76	1.25	1.09	0.58	+0.60	+1.07
30	26	17	9	3.6	0	4	12	21	27.5	100
+1.77	+0.97	+0.15		0.33	0.67	1.19	1.55			
30	15	6		0	6	15	30			
R.R. SPIKE N. SIDE 300 mm ELM										
24.4 m RT Sta 3+181										
0.91	1.55	1.52	2.32	1.74	2.4	1.28	0.91	0.58	+0.37	
30	23	12	3.6	0	4	16.5	18	25	100	
1.73	3.05	3.63	4.27	3.81	3.63	3.57	4.11			
30	21	12.8	3.6	0	6	15	30			
0.58	3.05	1.55	2.80	2.38	2.96	2.16	1.65	0.49		
30	23	14	4.3	0	3.3	12	21	30		